



# HYDROXPLAST WATERBORNE FOR EXTERIOR PLASTICS



1K PRODUCT FOR  
EXTERIOR PLASTICS

HIGH OUTDOOR  
DURABILITY

APPLICATION  
VERSATILITY

AJ1330/NN neutral  
AJ1330/BB white

# HYDROXPLAST WATERBORNE FOR EXTERIOR PLASTICS AJ1330/NN-BB

**AJ1330/XX** converter is a waterborne topcoat for outdoor use and it's the ideal solution for plastic substrate such as PVC.

Available in 30 gloss, in **neutral (/NN)** and **white (/BB)** bases it can be tinted with standard waterborne pastes of series XA2006/XX.

Prior to application it is necessary to remove the grease from the substrate using the specific thinner **DT1150/00**, **DT0015/00**, **DT0013/00**.

**AJ1330/XX** exhibits good thixotropy and can be applied even vertically in thick coats (max. 225 g/m<sup>2</sup> wet) with no sagging. Addition of pigment pastes may reduce hold up, requiring application of lower film weights.

## TECHNICAL CHARACTERISTICS

<b>APPLICATION</b>	Spray (conventional, airmix, airless and electrostatic)	
<b>DRYING TIME</b> (120 g/m <sup>2</sup> at 20°C)	Dust free	40'
	Touch free	2 h
	Sanding	6 h
	Stacking	24 h
<b>FORCED AIR DRYING</b> (120 g/m <sup>2</sup> )	Flash off	20'
	Hot air at 40°C	120'
	Cooling	20'
<b>AREA OF USE</b>	PVC window frames and wooden parts exposed outdoor	

Technical Service: Ph. +39 051 770770 - Fax +39 051 770521 customerservice@sayerlack.com

**Sherwin-Williams Italy S.r.l. - Export Department**  
Via del Fiffo 12 - 40065 Pianoro (BO) - Italia  
Ph. +39 051 770511 - Fax +39 051 770528  
export@sayerlack.it - www.sayerlack.com



Sayerlack is a brand of The Sherwin Williams Company