



# SAYERLACK®

## METAL & PLASTIC

### GENERAL INDUSTRIAL

#### Air drying

*Solvent based*

##### MU0302/XX

Anticorrosion primer



##### MS5090/00

Air drying glossy enamel



##### MS5030/00

Air drying matt enamel



*Water based*

##### MT0502/XX

Air drying anticorrosion primer



##### MA0522/04

Wash primer



##### MT5280/XX

Air drying glossy enamel



#### Two component

*Solvent based*

##### MB0360/XX

High adhesion epoxy primer



##### MB0400/02

Anticorrosion primer for thick application



##### MZ2280/00

Polyurethane acrylic glossy enamel



*Water based*

##### MA0550/XX

Epoxy primer



##### MA0510/XX

Anticorrosion epoxy primer



##### MZ5830/XX

Polyurethane acrylic enamel



##### MZ5880/XX

Polyurethane acrylic enamel



##### MZ5980/XX

Polyurethane acrylic enamel with direct adhesion



All the converters are compatible with Sayerlack Wood Color tinting pastes



## ACRYLIC SYSTEM

### Universal system for general industry and retail

#### MU7001/XX

High adhesion anticorrosion polyurethane acrylic primer  
 Can be used as matt DTM  
 HARDENER 20% weight ratio



#### MU0411/02

Sandable polyurethane acrylic filler  
 HARDENER 25% weight ratio



#### MZ2280/00

Glossy polyurethane acrylic enamel  
 HARDENER 50% weight ratio



#### MZ60XX/00

Polyurethane acrylic DTM with anticorrosion properties  
 10-50-80 gloss available  
 HARDENER 20-25% weight ratio, according to gloss level



### Lightfast hardeners

**MH2500/00** Standard

**MH2501/00** Fast

### Thinner

**MD0200/00** Recommended q.ty 0-25%  
 according to the chosen  
 application method

All the products of this system have direct adhesion on ferrous, non ferrous and several plastic substrates.  
 A preliminary test is recommended in case of applications on plastic and on any other pre-treated substrate.

## All the converters are compatible with Sayerlack Wood Color tinting pastes

All the technical information mentioned in this document are to be considered indicative.  
 For more information please refer to the TDS of the products or contact our technical service.

#### PICTOGRAM LEGEND:

DRYING TIME



BRUSH



ROLLER



SPRAY



DIRECT TO METAL



PACK. SIZES



#### Sherwin-Williams Italy S.r.l.

Via del Fiffo 12 - 40065 Pianoro (BO) - Italia  
 Tel. +39 051 770511 - Fax +39 051 777437  
 info@sayerlack.it - www.sayerlack.it

#### Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffo 12 - 40065 Pianoro (BO) - Italy  
 Tel. +39 051 770511 - Fax +39 051 770528  
 export@sayerlack.it - www.sayerlack.com

#### Servizio Clienti / Technical Service

Tel. +39 051 770770 - Fax +39 051 770521  
 servizioclienti@sayerlack.it / customerservice@sayerlack.com