

FINISHOIL



OIL-BASED
COATINGS



 **SAYERLACK**[®]
INNOVATIVE WOOD SOLUTIONS

With their continuous search for solutions for a healthier environment using natural materials, sustainable work processes, renewable energy and non-toxic finishes, Sayerlack is raising awareness that wood can be treated with oil-based products.

Treating wood with an oil-based finish is an excellent alternative as it enhances its character and is particularly suitable for people who love natural beauty with all of its flaws, as the finish changes and ages together with the wood.

For certain uses, oil-based finishes are often the most appropriate choice. In fact, they behave differently to traditional coatings, as they dry very slowly and do not simply cover the surface but soak deep into the wood's fibres.

This mechanism allows the aesthetic features of wood to be preserved and helps it conserve its natural colour.

The opportunity to repeat the treatment with the same product whenever necessary also makes an oil-based treatment a versatile and user-friendly solution.



OLV2322/00 100% NATURAL OIL

The **natural oil OLV2322/00 is ideal for preserving woods of all types, both solid and veneered.** It is absorbed deep into the fibres, reviving the wood, giving it a subtle sheen and enhancing the grain. The product is ready to use and easy to apply using a brush, rag, spray gun or immersion. **OLV2322/00** is made from 100% natural and bio-compatible substances. Items treated with OLV2322/00 require regular maintenance with the same product. The intervals between these treatments depends on the environmental conditions the finished article is exposed to.

AOV2343/00 WATERBORNE OIL FOR INTERIOR

The **waterborne wax-effect oil AOV2343/00 is designed for treating indoor furniture and parquet flooring.** It can be applied using a spray gun, brush or rag and as **AOV2343/00** is a waterborne oil with a natural fragrance of beeswax it leaves wood looking soft, natural and waxy. As with solvent-based oils, maintenance should be carried out according to the wear the item is subjected to. **AOV2343/00** can be mixed with 5% of **AH1564/00** to increase the product's adhesion and chemical resistance while maintaining its long pot-life. We suggest adding the hardener when treating parquet or when a surface that has already been treated needs renovating to achieve maximum performance.

AOV2343/00 can be coloured using stains and/or pigments from the **AC2110/XX, AC0600/XX, AC1810/XX, XA2006/XX** and **XA4034/XX** series.

AO3805/00 WATERBORNE OIL FOR WOOD DECKING

The **waterborne oil AO3805/00 is ideal to treat thermotreated wood or bamboo composite material for decking.** These substrates are generally very difficult to treat and might show an early degradation. If not properly protected, the sun has a fast effect on them. Using the suitable protective product is the only solution to reach the performances of durability and stability that substrates of this kind can provide.

Pigmentation with **XA4034/XX** or **XA2006/XX** is also highly recommended.

OL30xx/00 PARQUET OIL

The **wood oil OL30xx/00 has been created specifically for indoor and outdoor parquet sector.** The product can be applied using a roller, brush, rag or spray gun. It has a high viscosity, good chemical and physical resistance and quick drying properties. In case of use on outdoor deck, it is advisable to apply a first coat of a tinted wood stain. Annual maintenance is recommended. It is available in 10 and 30 gloss, and can be coloured using the **XEL3609/XX** and **XE4150/XX** pastes.

OL3300/00 MAINTENANCE OIL

Developed for **quick and easy maintenance of exterior and interior wooden items,** this general use oil can be used for flooring, swimming pools borders, benches and garden furniture. Thanks to its blend of natural oils **OL3300/00** has excellent substrate penetration and provides good protection against water. Can be applied by brush then, after a minute or so, wipe with a dry cloth so as to ensure even absorption. For best results apply two coats and then maintain the surface and appearance with an annual application.



Easy-to-apply systems that naturally strengthen and enliven timber are so often requested for wooden items that Sayerlack has brought together a series of high quality components to create its oil-based FINISHOIL products: a range that can satisfy all the market's main requirements.

OL40xx/XX LIGHT FAST OIL

The **light fast oil OL40xx/XX** is a combination of white **OL4030/13** and clear **OL4010/00**. This system allows to get white or white-based colors with oil application and to protect them with a light fast clear. Other solventbased oil tends to yellow not only because of the sunlight, but also because of the natural oxidation of the components of the products. A final clear layer is recommended to obtain a better resistance to dirt pick up. Toning of the color is possible with **XEL3609/XX** and **XE4150/XX** pastes.

OLL3904/00 NATURA-OIL

The **natura-oil OLL3904/00** is ready to use and the **ideal choice for parquet flooring**. Characteristics of easy application and building power make it perfect for mechanical buffing on large surfaces. The product can be colored using the pastes of series **XEL3609/XX** and **XE4150/XX**. Enhancing the grain of the wood is possible through brushing.

OLL3645/00 WAXY OIL

The **wax-effect oil OLL3645/00** can be used for panels, **indoor furniture, frames, and skirting boards**. It can be applied by spray gun, brush and rag. **OLL3645/00** is composed by a mix of special oils and selected waxes. It is especially designed for a simple and rapid application, providing good protection to wood, an extremely natural look and a soft waxy finish. Pigmentation is possible with the pastes of series **XEL3609/XX** and **XE4150/XX**.

OLL3729/00 OIL FOR EXTERIOR

OLL3729/00 is a urethane oil developed for exterior application to outdoor furniture, decking and coverings in general. It has good wettability of wood, along with excellent application workability and good resistance against weathering. To make it suitable for a widest range of substrates we have selected special raw materials that make this product the ideal choice also for thermo treated wood. For better results we recommend 2 coats to be applied by brush or spray followed by wipe to ensure even absorption. Annual applications of **OLL3729/00** will maintain the appearance and prolong the life of all outdoor wooden artefacts. Pigmentation with the pastes of series **XEL3609/XX** or **XE4150/XX** is highly recommended to achieve the suitable sunlight resistance.

FINISHOIL

Sherwin-Williams UK Coatings Ltd.

A1 Business Park - Knottingley
West Yorkshire - WF11 OBU - England
Ph. +44 (0) 1977 673363 - Fax +44 (0) 1977 673521
ukinfo@sherwin.com - www.sayerlack.co.uk

Sherwin-Williams (S) Pte. Ltd.

8 Admiralty Street #07-08, Admirax
757438 - Singapore
Ph. +65 6763 7789 - Fax +65 6763 0252
infoasia@sayerlack.it - www.sayerlack.com

Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffo 12 - 40065 Pianoro (BO) - Italy
Ph. +39 051 770511 - Fax +39 051 777528
export@sayerlack.it - www.sayerlack.com

Technical Service:

Ph. +39 051 770770 - Fax +39 051 770521
customerservice@sayerlack.com



Sayerlack is a brand of The Sherwin Williams Company